Table des matières

Script d'optimisation automatique des bases 3

Script d'optimisation automatique des bases

Ce script optimise les bases de données MySQL présentes sous `/var/lib/mysql`.

```
#!/bin/bash

for base in `ls -l /var/lib/mysql/|grep dr|grep -Ev "test|status|mail|dumps"|awk '{print $NF}'`
do
echo "use $base;" > /tmp/optmz_${base}.sql
echo -e "OPTIMIZE TABLE \c" >> /tmp/optmz_${base}.sql
        for table in `ls -1 /var/lib/mysql/$base/*.frm|awk -F "/" '{print $6}'|awk -F "." '{print $1}'`
        do
        echo -e "$table,\c" >> /tmp/optmz_${base}.sql
        done
echo ";" >> /tmp/optmz_${base}.sql
cat /tmp/optmz_${base}.sql|sed "s/,;/;/g" > /tmp/optmz_${base}.sql.temp
mv /tmp/optmz_${base}.sql.temp /tmp/optmz_${base}.sql
done

for file in `ls -1 /tmp/optmz*.sql`
do
mysql -u ''user'' --password=XXXXXXXX < $file #''user'' doit avoir les droits full
done

rm -f /tmp/optmz*.sql
```

From:
https://unix-bck.ndlp.info/ - **Where there is a shell, there is a way**

Permanent link:
https://unix-bck.ndlp.info/doku.php/informatique:base_de_donnees:script_d_optimisation_automatique_des_bases

Last update: **2009/06/29 19:04**