

Table des matières

- [Bootable ISO from NIM](#)

Récupérer infos open firmware

```
Another method:
0 > dev packages/gui
ok
0 > display_boot_devices #network

SMS Macro Operation Succeeded.
Device Current Device
Number Position Name
1. 2 Interpartition Logical LAN ( loc=U8246.L2B.06009AA-V1-C3-T1 )
2. - Interpartition Logical LAN ( loc=U8246.L2B.06009AA-V1-C4-T1 )
3. - Interpartition Logical LAN ( loc=U8246.L2B.06009AA-V1-C5-T1 )
4. - Interpartition Logical LAN ( loc=U8246.L2B.06009AA-V1-C6-T1 )
5. - PORT - 1 IBM Host Ethernet Adapter ( loc=U78AB.001.WZSGK0Z-P1-C2-T1 )
6. - PORT - 2 IBM Host Ethernet Adapter ( loc=U78AB.001.WZSGK0Z-P1-C2-T2 )
ok
0 > display_mac_address U78AB.001.WZSGK0Z-P1-C2-T1
SMS Macro Operation Succeeded.
MAC-ADDRESS = 5cf3fc85f240
ok
```

From:
<https://unix-bck.ndlp.info/> - **Where there is a shell, there is a way**

Permanent link:
https://unix-bck.ndlp.info/doku.php/informatique:nix:ibm:ibm_aix_nim

Last update: **2018/03/27 10:50**