Table des matières

Mirror root 3
Créer device mirroré 3
Retirer une patte 3
Remirrorer suite à remplacement de disque 3

Mirror root

```
prtvtoc /dev/rdsk/c1t0d0s2 | fmthard -s - /dev/rdsk/c1t1d0s2
metadb -a -c 3 -f c1t0d0s7 c1t1d0s7
metainit -f d11 1 1 c1t0d0s0
metainit -f d12 1 1 c1t1d0s0
metainit d10 -m d11
metaroot d10
init 6
metattach d10 d12
```

Créer device mirroré

```
metadb -a -f c0t2d0s1
metadb -a -f c0t3d0s1
metadb -a -c2 c0t2d0s1 c0t3d0s1
metainit d21 1 1 c0t2d0s1
metainit d22 1 1 c0t3d0s1
metainit d20 -m d21
metattach d20 d22
```

```
bash-3.00# metastat d2
d2: Mirror
    Submirror 0: d12
      State: Okay
    Submirror 1: d22
      State: Okay
    Pass: 1
    Read option: roundrobin (default)
    Write option: parallel (default)
    Size: 32768000 blocks (15 GB)

d12: Submirror of d2
    State: Okay
    Size: 32768000 blocks (15 GB)
    Stripe 0:
        Device     Start Block  Dbase        State Reloc Hot Spare
        c0t2d0s0          0     No            Okay   Yes


d22: Submirror of d2
    State: Okay
    Size: 32768000 blocks (15 GB)
    Stripe 0:
        Device     Start Block  Dbase        State Reloc Hot Spare
        c0t3d0s0          0     No            Okay   Yes


Device Relocation Information:
Device   Reloc  Device ID
c0t2d0   Yes    id1,sd@SSEAGATE_ST973401LSUN72G_2211NLEJ____________3LB1NLEJ
c0t3d0   Yes    id1,sd@SSEAGATE_ST973401LSUN72G_2211NGQR____________3LB1NGQR
```

Retirer une patte

```
metadetach -f d20 d21
metadetach -f d30 d31
metadetach -f d10 d11
metaclear d11
metaclear d21
metaclear d31
```

Remirrorer suite à remplacement de disque

```
metareplace -e dX c0t0d0sX
```

From:
https://unix-bck.ndlp.info/ - **Where there is a shell, there is a way**

Permanent link:
https://unix-bck.ndlp.info/doku.php/informatique:nix:solaris:solaris_sds

Last update: **2015/12/16 09:13**