Table des matières

Identifier un switch et le port associé à une interface réseau 3

Identifier un switch et le port associé à une interface réseau

- **tcpdump - CDP**

```
tcpdump -nn -v -i eth3 -s 1500 -c 1 'ether[20:2] == 0x2000'
```

```
Device-ID (0x01), length: 24 bytes: 'nom_du_switch'
Port-ID (0x03), length: 21 bytes: 'GigabitEthernet1/0/10'
```

- **tcpdump - LLDP**

```
[root@ex1dc1dbadm01 ~]# tcpdump  -i eth9 -c 1 '(ether[12:2]=0x88cc or ether[20:2]=0x2000)'
dropped privs to tcpdump
tcpdump: verbose output suppressed, use -v or -vv for full protocol decode
listening on eth9, link-type EN10MB (Ethernet), capture size 262144 bytes
17:12:16.774487 CDPv2, ttl: 180s, Device-ID 'STK-EXADATA-PA3.nibclt.prod', length 429
1 packet captured
2 packets received by filter
0 packets dropped by kernel
```

- **snoop**

```
snoop -d <interface> -x0 -v 'ether[20:2] = 0x2000'
```

- **nmap**

```
nmap -sP 192.168.1.1/24
```

From:
https://unix-bck.ndlp.info/ - **Where there is a shell, there is a way**

Permanent link:
https://unix-bck.ndlp.info/doku.php/informatique:reseau:tips

Last update: **2025/02/25 16:14**